

Type		OHPA-08130-S AC
Order number		212 098
EAN-Code 4026187...		193157
Power supply		2 hot plug AC
Type		OHPA-08130-S DC
Order number		212 099
EAN-Code 4026187...		196530
Power supply		2 hot plug DC
RF and optical characteristics		
Optical output power (P _{tot})	[dBm]	+13,0 ± 0,5
Number of optical output ports		4
Optical connector type		SC/APC
Optical input wavelength	[nm]	1550 ± 15
Rated optical input power range	[dBm]	-3... +10 (details see order information)
Output power variation	[dB]	± 0,5
Noise figure (P _{in} =0 dBm, λ=1550 nm)	[dB]	≤ 5
Return loss at input	[dB]	≥ 45
Return loss output	[dB]	≥ 45
Optical output adjustable range	[dB]	-3 ..0
Laser switch off/on		by key lock on front for installation purposes
Common data		
Management		SNMP and web interface
Chassis type		1 RU, 19" rack mounted
Power supply	[pcs]	2 hot plug / AC or DC
AC Power supply	[VAC]	150 - 265
DC Power supply	[VDC]	-36 .. 72 (on request)
Power consumption	[W]	≤ 60
Dimensions (W x H x D)	[mm]	483 x 44 x 380 (1 RU)
Ambient temperature	[°C]	-10 .. +45
Maximum operating humidity	[%]	95% no condensing
Storage temperature range	[°C]	-30 .. +75
Maximum storage humidity	[%]	95% no condensing