

Type		U 168-X
Order number		380 172
EAN-Code		4026187194505
Number of DVB-CT2 input signals		4
Number of DVB-CT2 tuners		8
Number of IP output streams		8 MPTS, 504 SPTS
Interfaces		
Management		2 x 100 Base-T Ethernet (RJ 45)
Data		2 x 1000 Base-T Ethernet (RJ 45)
Protocols		IEEE802.3 Ethernet, RTP, ARP, IPv4, TCP/UDP, HTTP, SNMP, IGMPv3
Transportstream Encapsulation		
Protocols		UDP, UDP / RTP, 1-7 packets, FEC
Packet length	[Bytes]	188 / 204
DVB-C demodulator		
Frequency range	[MHz]	47 - 862
Input data rate	[Mbaud]	0,5 - 7
Modulation modes (accord. DVB-standard)		QPSK, QAM16, QAM32, QAM64, QAM128, QAM256
Input symbol rate	[MS/s]	1,8 - 7,2
DVB-T demodulator / DVB-T2 demodulator (Scrambling of L1 post signalling; conforms to ETSI EN 302-755 v1.31)		
Frequency range	[MHz]	47 - 862
Modulation		DVB-T: 4-, 16-, 64-QAM; DVB-T2: 4-, 16-, 64-, 256-QAM DVB-T2 scrambling of L1 post signalling
Guardinterval		DVB-T: 1/4; 1/8; 1/16; 1/32; DVB-T2: 1/4; 5/32; 1/8; 5/64; 1/16; 1/32; 1/64; 1/128
FEC		DVB-T: 1/2; 2/3; 3/4; 5/6; 7/8; DVB-T2: 1/2; 3/5; 2/3; 3/4; 4/5; 5/6
FFT-Mode		DVB-T: 2k, 8k; DVB-T2: 1k, 2k, 4k, 8k, 16k, 32k
Bandwidth	[MHz]	DVB-T: 6; 7; 8; DVB-T2: 5; 6; 7; 8
Remote voltage supply		5V, typical, 100mA, switchable
Input symbol rate	[MS/s]	DVB-T: 6, 7, 8; DVB-T2: 5, 6, 7, 8
RF inputs		
Connectors	[Ω]	75, 2 x F-jack
Common data		
Current consumption at 48 V	[mA]	710
Power consumption at 36 - 60 V	[W]	34 per module
Input voltage	[V]	36 - 60
Dimensions		1 HU, 19 inch
Ambient temperature	[°C]	0 ... +45