

Type		V 212	V 212 CI
Order number		380 203	380 201
EAN-Code		4026187680077	4026187680206
AS input			
Inputs	[Ω]	MCX-Buchse / BNC am Gehäuse, 75	
Connectors		2 x DVB ASI	
Bitrate	[MBit/s]	max. 67 netto	
Transmission mode		Packet burst / continuous	
Packet length		188, 204	
Reed-Solomon Decoding		optional in 204	
CI interfaces		-	☒
HF modulator			
kanalselektive Ausgangsfilter steckbar		☒	
Connectors	[Ω]	IEC-Buchse, 75	
Frequency range	[MHz]	47 - 862 (K2 - K69)	
Output level	[dBμV]	90...100, adjustable	
Intermodulation distance	[dB]	typ. 60	
Return loss	[dB]	> 10	
Spurious frquency distance	[dB]	typ. 60	
Intercarrier signal to noise ratio	[dB]	typ. 60	
Stereo cross talk	[dB]	> 55	
Residual carrier accuracy	[%]	1	
TV standard	[dB]	PAL/SECAM, B/G/D, SECAML, A2/NICAM	
Video-signal to noise ratio	[dB]	typ. 60	
Allgemeine Daten			
Power consumption	[W]	11	13,5
Ambient temperature	[°C]	0...+50	