

Type		V 252	V 253 CI
Order number		380 217	380 271
EAN-Code		4026187680268	4026187131463
DVB-S2 demodulator			
Connectors	[Ω]	F-jacks, 75	
Input frequency range	[MHz]	950 - 2150	
Input level	[dBμV]	40 - 80	
Input symbol rate	[MS/s]	max. 30,0 (DVB-S2); max. 45,0 (DVB-S)	
DVB-S Viterbi		1/2, 2/3, 3/4, 5/6, 7/8	
DVB-S2 LDPC		1/4; 1/3; 2/5; 1/2; 3/5; 2/3; 3/4; 4/5; 5/6; 8/9; 9/10	
DVB-S2 Roll-off-factors		0,20; 0,25; 0,35	
DVB-S2 modulation		QPSK, 8PSK	
ASI output			
Connectors	[Ω]	F-jacks, BNC at chassis	MCX jack, 75
Outputs		6 x ASI	4 x ASI
Data rate	[MBit/s]	270	
Transmission modes		Packet burst / continuous	
Packet length		188 / 204	
TS editing			
Data rate adjustment		-	☒
PCR correction		-	☒
NIT handling		-	☒
PID filtering / remapping		-	PID remapping
Service filtering		-	Online Pass- / Drop filter
CI interfaces		-	☒
Common data			
Power consumption	[W]	9,5	11,5
Ambient temperature	[°C]	0...+50	